

WHAT IS CLAIMED:

Sub A3) 1. Fastening arrangement for a module for the fastening of the module on a vehicle body,

wherein fastening points of the module are constructed as a plurality of elongated openings extending in the same direction.

2. Fastening arrangement according to Claim 1, wherein the elongated openings are constructed at least partially as a curved path.

3. Fastening arrangement according to Claim 2, wherein end areas of the curved paths are directed into a mounting position of the module against the gravitational force.

4. Fastening arrangement according to Claim 2, wherein the curved paths are constructed such that a movement of the module is achieved during the mounting operation.

Sub A3) 5. Fastening arrangement according to Claim 3, wherein the curved paths are constructed such that a movement of the module is achieved during the mounting operation.

A3 6. Fastening arrangement according to Claim 1,
wherein, on at least one of the elongated openings,
at least one flank of the elongated opening is constructed as
an insertion aid.

7. Fastening arrangement according to Claim 2,
wherein, on at least one of the elongated openings,
at least one flank of the elongated opening is constructed as
an insertion aid.

8. Fastening arrangement according to Claim 3,
wherein, on at least one of the elongated openings,
at least one flank of the elongated opening is constructed as
an insertion aid.

9. Fastening arrangement according to Claim 4,
wherein, on at least one of the elongated openings,
at least one flank of the elongated opening is constructed as
~~an insertion aid.~~

Sub A3 10. Fastening arrangement according to Claim 5,
wherein, on at least one of the elongated openings,
at least one flank of the elongated opening is constructed as
an insertion aid.

11. Fastening arrangement according to Claim 1,

A3
wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

12. Fastening arrangement according to Claim 2,

wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

13. Fastening arrangement according to Claim 3,

wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a

vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

14. Fastening arrangement according to Claim 4,

wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

Sub 137 15. Fastening arrangement according to Claim 5,

wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

16. Fastening arrangement according to Claim 6,

wherein the module comprises a radiator with air guiding elements placed upstream and downstream, which are held in a module frame, wherein an opening is provided on one of the air guiding elements, which opening, in the mounted position of the module, rests on a corresponding opening of a vehicle body, a plane of the openings being arranged essentially perpendicularly with respect to a mounting plane of the module.

17. A method of fastening a vehicle radiator module to a vehicle using the fastening arrangement of Claim 1.

18. A method of fastening a vehicle radiator module to a vehicle using the fastening arrangement of Claim 11.

19. A vehicle assembly comprising a vehicle body having a plurality of protruding fastening lugs, and a module including a module frame with a plurality of fastening openings engageable over the fastening lugs,

wherein said fastening openings are elongated openings extending parallel to one another to facilitate placement of said module with said module frame fastening openings surrounding the respective fastening lugs, and adjusting sliding movement with the module transverse to the

A3 ~~fastening lugs to an installation position while supported at the fastening lugs.~~

20. ~~A vehicle assembly according to Claim 19,
wherein at least one of said elongated openings is curved so as to secure the module frame and module against gravity when in a preassembled position and during transverse sliding of the module frame to an installation position.~~

Sub A3) 21. ~~A vehicle assembly according to Claim 20,
wherein at least one of the elongated curved openings is open laterally to accommodate insertion of the module frame laterally over a corresponding fastening lug.~~

22. ~~A vehicle assembly according to Claim 19,
wherein said module includes a radiator and air guiding elements held on the module frame.~~

23. ~~A vehicle assembly according to Claim 21,
wherein said module includes a radiator and air guiding elements held on the module frame.~~

A03 24. A method of assembling a module at a vehicle body having a plurality of protruding fastening lugs, said method comprising:

providing said module with a module frame having a plurality of elongated openings,

placing the module frame with said elongated openings over the respective fastening lugs,

slidably moving the module frame laterally to an installation position while supported at the fastening lugs, and

fastening the module frame to the vehicle body with clamping means on said fastening lugs.

25. A vehicle assembly according to Claim 24,

wherein at least one of said elongated openings is curved so as to secure the module frame and module against gravity when in a preassembled position and during transverse sliding of the module frame to an installation position.

Pub A3 26. A vehicle assembly according to Claim 25,

wherein at least one of the elongated curved openings is open laterally to accommodate insertion of the module frame laterally over a corresponding fastening lug.

A3

Add A3)

42370a	42370b	42370c	42370d	42370e	42370f	42370g	42370h	42370i	42370j	42370k	42370l	42370m	42370n	42370o	42370p	42370q	42370r	42370s	42370t	42370u	42370v	42370w	42370x	42370y	42370z
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
15	16	17	18	19	20	21	22	23	24	25	26	27	28												